

# SLURRYTUB™



BETTER FOR THE ENVIRONMENT



## FACT SHEET: WHY SHOULD YOU USE SLURRYTUB?

### AN ENVIRONMENTAL SOLUTION FOR THE DISPOSAL OF SLURRY WASTE

SLURRYTUB IS A SIMPLE AND PORTABLE 'FILTER SYSTEM' DESIGNED TO PROTECT THE ENVIRONMENT AND SURROUNDING ECOSYSTEMS FROM CONTAMINATION. IT ALSO PROTECTS THE HOME OWNERS' (YOUR CLIENTS) LAWNS/GARDENS, SURROUNDING STORMWATER SYSTEMS AND EXPENSIVE TO MAINTAIN SEWER PIPES FROM BEING BLOCKED BY SOLIDIFYING CEMENT SLURRY.



#### How much does SLURRYTUB hold?

SLURRYTUB can hold up to 35 - 50L (13 gallons) of wet trade waste material. Typically enough from a standard wheelbarrow.

#### How long does it take SLURRYTUB to drain?

The filters perform best when washing out CEMENT based material and will usually drain between 30 - 45 mins (depending on the volume and type of material).

**PLEASE NOTE: Washing up with SLURRYTUB after using some adhesives/grouts, elastic sealants/coatings, floor levelling compounds and any finer sediment material WILL slow the draining speed. Users should allow extra time for the draining/drying process.**

#### Is SLURRYTUB suitable for ALL wash out materials?

The filter has been designed to capture cementitious solids in most wash water down to 25-28 microns.

**PLEASE NOTE: Some waterproofing sealants, adhesives and polymers along with finer sediment will slow down the drainage speed. The filter is performing its function and users should allow for the extra drainage time.**

#### Where do I let the filtered water drain?

You should always allow the filtered water from SLURRYTUB drain into a protected wash up area or be captured and recycled on the job. This a great way to increase water savings on your jobsite.